

# **Declaration of Performance**

# No. L009 CPR 3-12-14

1.) Unique identification code of the product type

# Laticrete Masonry Veneer Mortar [255]

2.) Type, batch or serial number or any other element allowing identification of the construction product

## DS-255.0-0813

3.) Intended use or uses of the construction product, in accordance with the applicable harmonized technical specification, as foreseen by the manufacturer.

## Patented, lightweight versatile polymer modified thin-set

4.) Name, registered trade name or registered trade mark and contact address of the manufacturer as required under article (11)5:

#### LATICRETE International, Inc. 1 LATICRETE Park North Bethany, CT 06524-3423 USA

5.) Where applicable, the name and contact address of an authorized representative may be stated

6.) System of assessment and verification of constancy of performance of the construction product as set out in Annex V:

## System 3

7.) In the case of the declaration of performance concerning a construction product covered by the harmonized standard

# EN 12004:2007 + A1:2012

#### The Notified Body Lucideon (Previously Named Ceram) NB 1289 performed the Initial Type Testing under system 3 and issued the following report: Test report (141610)-7308

LATICRETE International, Inc. • One LATICRETE Park North, Bethany, CT 06524-3423 USA • Tel +1.203.393.0010 • Toll Free 1.800.243.4788 • Fax +1.203.393.1684 • www. laticrete.com



#### **Globally Proven Construction Solutions**

#### 8) Declared Performance

Essential characteristics	Performance	Harmonised technical specification
<ul> <li>Bond strengths as:</li> <li>Initial tensile adhesion strength -</li> <li>Initial tensile adhesion strength – after water immersion</li> <li>Initial tensile adhesion strength – after heat aging</li> <li>Initial tensile adhesion strength – after freeze/thaw cycles</li> </ul>	> 1.0 N/mm2 > 1.0 N/mm2 > 1.0 N/mm2 > 1.0 N/mm2	
Open time tensile adhesion strength:		EN 12004:2007 + A1:2012
Tensile strength after 20 minutes open time	> 0.5 N/mm2	
Reaction to Fire	NPD	
Reduced Slip	< 0.5mm	
Release of dangerous substances	See MSDS	

9) The performance of the products identified in points 1 & 2 is in conformity with the declared performance in point 8.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

#### Signed for & on behalf of the manufacturer by:

Sean Boyle, Director. Marketing & Product management

On: 03-12-2014

Laticrete International Inc. 1 LATICRETE Park North, Bethany, CT 06524-3423 USA