

VERSION 2 - CLP-GHS CLASSIFICATIONS (EC) No. 1272/2008



Ref: PG/2

# 1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND COMPANY:

Product Name: LATICRETE MVIS Premium Pointing Mortar

**1.2 Applications:** For grouting joints around tile & stone.

1.3 Supplier: Laticrete UK Ltd; Speke Hall Industrial Estate; Speke; Liverpool; L24 1YA

Tel: 0151 486 6101; Fax 0151 448 1982

e-mail: sales@lataicrete.co.uk; web: www.laticrete.co.uk

**1.4 Emergency Telephone No.** Tel: 0151 486 6101

#### 2. HAZARDS IDENTIFICATION:

**2.1 Classification:** Not Classified as hazardous

(1999/45/EEC)

Risk phrases: N/A

Safety phrases: S2 Keep out of the reach of children.

Avoid breathing dust.

S24/25 Avoid eye and skin contact

Classification : (EC 1272/2008) 2.2 Label elements:

Key Word: N.A

Hazard statements: Not classified as hazardous Precautionary statements: P102 Keep out of reach of children.

P260a Do not breathe dust.

P280f Wear protective gloves, eye and face protection.

P501a Dispose of contents/container in accordance with local regulations.

Supplementary precautionary

**statements:** P362 Take off contaminated clothing and wash before reuse.

P403+233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

2.3 Other hazards: Inhalation of silica dust may not cause noticeable injury or illness even though permanent lung

damage may be occurring. Persistent inhalation of silica dust may have long-term serious chronic

health effects if recommended protective controls are ignored:

# 3.1 Substances:

Name:	CAS No.:	Concentration:	Classification: (EC 1272/2008)
Silica sand	80878-86-0 2-3	40.0 – 60.0 %w/w	n/a
Calcium Aluminate	65997-16-2	20.0 – 30.0 %w/w	n/a
Calcium Sulphate	7778-18-9	5.0 - 10.0% w/w	n/a
Octyl Isithiazolinone	26530-20-1	< 0.1% w/w	H311; H314; H331; H400; H410



VERSION 2 - CLP-GHS CLASSIFICATIONS (EC) No. 1272/2008



# 4. FIRST AID MEASURES:

4.1 Description of measures:

EYE CONTACT: Do not rub eye. Immediately flush with plenty of water for up to 15 minutes. Remove any contact

lenses and open eyelids. If irritation persists: Continue flushing during transport to hospital.

INHALATION: Remove affected person to fresh air. If nose or airways become inflamed or breathing difficulties

occur and irritation persists seek medical attention.

SKIN CONTACT: Remove contaminated clothing immediately and wash skin with soap and water.

In case of rashes, wounds or other skin disorders: Seek medical attention.

INGESTION: Clean out mouth with copious volumes of water and drink plenty. Do not induce vomiting. Seek

medical attention if mouth is inflamed.

4.2 Acute & Chronic symptoms:

**Inhalation:** Frequent inhalation of large quantities of cement dust over a long period of time increases the

risk of developing lung diseases. Silica dust may irritate throat and respiratory system and cause coughing. Frequent inhalation of dust over a long period of time increases the risk of

developing lung diseases.

Ingestion: May cause irritation in mouth and throat. Small amounts due to normal handling will have little or

no effect.

Skin contact: No known adverse effects under normal conditions of use although persistent unattended skin

contact may induce redness.

**Eye Contact:** 

Eye contact with cement (dry or wet) may cause serious and potentially irreversible injuries.

4.3 Immediate medical attention: See First Aid measures above

## 5. FIRE FIGHTING MEASURES:

5.1 Extinguishing media: All cement-based adhesives are non-flammable, although paper sacks may well smoulder &

combust. Use extinguisher appropriate to the surrounding materials & fire.

**5.2 Combustion Hazards:** Oxides of carbon and paper ash. During fire, toxic gases (CO, CO2) are formed.

**5.3 Advice for fire-fighters:** Wear self-contained breathing apparatus with full face piece and protective clothing

#### **6. ACCIDENTAL RELEASE MEASURES:**

**6.1 Personal protection:** Avoid inhalation of dust. Avoid contact with eyes and prolonged skin contact. Use work methods

which minimise dust production.

**6.2 Environmental precautions:** Contain spillage within a defined area and avoid discharge to watercourses and drains.

**6.3 Spill removal methods:** Ideally use an industrial vacuum cleaner and only brush residues when sprinkled with a

dampened absorbent (sawdust or granules) into sealable containers when wearing personal

protective equipment and ensuring adequate ventilation is available

6.4 References to other sections: Before attempting any clean-up operation, consult the requirements for protective equipment

shown in section 8 of this document.



VERSION 2 - CLP-GHS CLASSIFICATIONS (EC) No. 1272/2008



# 7. HANDLING & STORAGE:

7.1 Safe handling precautions: Lifting operations of no more than 1 case of 3 x 5kg sachets at a time.

7.2 (a) Safe storage conditions: Store in sealed, clearly marked sacks. Keep out of reach of children in a cool well-ventilated

> environment, preferably off the ground and out of contact with water. This product must be stored in unopened bags in cool dry conditions and protected from excessive draught. Protect containers against physical damage and check regularly for leaks. Observe manufacturers

storing and handling recommendations.

7.2 (b) Incompatible materials: Avoid exposure to moisture when in storage prior to use

7.3 Specific end uses: Construction material

### 8. EXPOSURE CONTROLS & PERSONAL PROTECTION:

8.1 Control parameters

Substance: 8 hour exposure limit Type: Source:

Total dust Respirable: 10.0 mg/M3 TWA **EH40** Silica dust: Respirable: 0.1mg/M3

Total dust inhalable: 5.0 mg/M3 TWA EH40

Silica dust: Inhalable: 0.1mg/M3

8.2 Exposure controls:

**Engineering controls:** Provide adequate ventilation. Observe occupational exposure limits and minimise the risk of

inhalation of dust by using contained ventilation where practical.

Respiratory protections: During dust-raising work: Use respiratory equipment with particle filter, type

P2. Or wear a BS rated disposable dust mask for each daily task.

Hand protection: Wear natural rubber gloves or gauntlets approved to EN 374 & EN 420

Dust proof BS 2092 Goggles or chemical grade visors are also advised Eye protection:

wherever there is a risk of dust or paste entering the eyes.

PVC overalls with long-sleeved elasticated cuffs and closed neck should be Other Protection:

worn and laundered immediately after use. Do not work in powder or paste

contaminated overalls.

Particular care should be taken to ensure that mixed grout does not enter the

Hygiene measures: Contact with skin must be washed off immediately











# 9. PHYSICAL & CHEMICAL PROPERTIES:

Appearance: Fine powder Relative density: 1.75 Kg/litre when mixed

< 1% Odour: Negligible Water solubility: Odour threshold: Solubility in oils: n/a n/a Partition coefficient (Kow): pH: 10.0 - 11.0 when mixed n/a Flash point: Auto-ignition temperature: n/a n/a

Melting point: Decomposition temperature: n/a n/a **Boiling point:** n/a Surface tension: n/a

Evaporation rate: Viscosity: 8000 - 15000 Mpa.s mixed n/a

Upper/Lower Flam limits: n/a **Explosive properties:** n/a Vapour pressure: Oxidising properties: n/a n/a

Vapour density: Particle size: Less than 300 micron



VERSION 2 - CLP-GHS CLASSIFICATIONS (EC) No. 1272/2008



#### 10. STABILITY & REACTIVITY:

**10.1 Conditions to avoid:** Humidity & moisture during storage **10.4 Reactivity:** Stable

10.2 Incompatible Materials: Not known 10.5 Chemical Aqueous media

reactivity:

**10.3 Decomposition hazards:** Stable **10.6 Risk of hazardous** Not known

reaction:

#### 11. TOXICOLOGICAL INFORMATION:

**11.1 Information on toxicological effects:** This product has not been exhaustively tested. Judgements on the expected toxicity of this product have been made based upon consideration of its' major components.

### Routes of exposure:

Inhalation, ingestion & contact with skin & eyes all have the potential for adverse effects on human organs when subject to acute and chronic levels of exposure. Chronic exposure to respirable dust in excess of occupational exposure limits may cause coughing, shortness of breath and may cause chronic obstructive lung disease (COPD).

### **Skin Corrosivity / Irritation:**

Based on available data, the classification criteria for skin corrsivity are not met. - Not irritating (OECD 404)

#### Eye damage/irritation:

Direct contact with dry cement may cause corneal damage by mechanical stress, or delayed irritation. Direct contact by larger amounts of dry cement or splashes cause effects such as minor eye irritation Not irritating (OECD 405)

#### Respiratory/skin sensitisation:

Not irritating (OECD 404) Not a skin sensitiser

#### 12. ECOLOGICAL INFORMATION:

**12.1 Ecotoxicity:** The product is not expected **12.4 Mobility in soil:** negligible

to be hazardous to the

environment.

12.2 Bio-accumulative potential: Not relevant 12.5 PBT and vPvB result: Not relevant

12.3 Persistence & degradability: After hardening, this mortar 12.6 Other adverse effects: Avoid contamination of

presents no toxicity risks. watercourses

### 13. DISPOSAL CONSIDERATIONS:

**13.1 Waste treatment Methods:** To be disposed in accordance with local authority regulations for builders waste.

Allow to harden, avoid entry in sewage and drainage systems or into bodies of water (e.g, streams) and dispose of according to the local legislation. Avoid entry into the sewage water system. Dispose of the hardened product as concrete waste. Due to the inertisation, waste

mortar is not classed as a dangerous waste.

#### 14. TRANSPORT INFORMATION:

# **Transport Labels:**

Cement based dry-pack mortars of this type are not covered by the international regulation on the transport of dangerous goods (IMDG, IATA, ADR/RID) and therefore no classification is required.

Regulatory Code (Land, Sea & Air): ADR IMDG ICAO

14.1 UN No.:

14.2 Proper shipping name:

14.3 ADR Packing Group:

14.4 Transport Hazard Class:

14.5 Environmental hazards.

14.6 Special user precautions:

14.7 Transport in bulk - IBC code:



VERSION 2 - CLP-GHS CLASSIFICATIONS (EC) No. 1272/2008



#### 15. REGULATORY INFORMATION:

#### 15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture

All components are listed as existing substances in Europe

#### **UK Regulatory References:**

Health and Safety at Work Act 1974. The Control of Substances Hazardous to Health Regulations 2002 (S.I 2002 No. 2677) with amendments. Chemicals (Hazard Information & Packaging) Regulations.

Environmental Listing - Control of Pollution Act 1974. Control of Pollution (Special Waste Regulations) Act 1980.

#### **Statutory Instruments:**

The Chemicals (Hazard Information and Packaging for Supply) Regulations 2009 (S.I 2009 No. 716).

Approved Code Of Practice Classification and Labelling of Substances and Preparations Dangerous for Supply.

#### **Guidance Notes:**

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

#### **EU Legislation:**

Dangerous Substance Directive 67/548/EEC.

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, including amendments. Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006 with amendments.

#### **National Regulations:**

Users of this product are reminded of their duties under the current Control of Substances Hazardous to Health Regulations and a suitable and sufficient assessment of all the risk should be undertaken before using this product. The guidelines given in the HSE publication COSHH ESSENTIALS - Easy Steps To Control Chemicals gives sound advice for deciding safe working control measures.

Authorisations (Title VII Regulation 1907/2006) - No specific authorisations are noted for this product. Restrictions (Title VIII Regulation 1907/2006) - No specific restrictions of use are noted for this product.

#### 15.2 **Chemical safety assessment**

A chemical safety assessment has not been carried out for this product.

#### **16. OTHER INFORMATION:**

Last revision date: 22-02-19

> SDS No.: PG/2

List of abbreviations used in this SDS:

CAS Chemical abstracts service

CLP Classification, labelling & packaging regulation (EC) No. 1272/2008

DSD Dangerous substances Directive 67/548/EEC DPD Dangerous Products Directive 1999/45/EC Persistent, Bio-accumulative & Toxic

REACH Registration, Evaluation, Authorisation & Restriction of Chemicals Regulation (EC) 1907/2006

vPvB Very Persistent, very Bio-accumulative

Volume VII Approved supply list; EH40; Croner; Bulk supplier data sheets References:

Classification methods:

H Phrases in section 3: H311; H314; H331; H400; H410

Training for workers:

The information supplied in this safety data sheet is intended to assist in the use of the above product without risk to safety Disclaimer: and health and is based on current knowledge and experience of the associated physico-chemical hazards. The data does

not signify any warranty with regard to the product's properties. This information may be used to assist in formulating a

COSHH risk assessment if applied at work. This data sheet complies with EC Directive 91/155EC